

industriepark 21 - 2220 heist-op-den-berg - belgium  
t +32 15 24 93 10 - f +32 15 24 29 30  
info@rowin.com - www.rowin.com

**Rowin**  
P L A S T I C S N V



# INDUSTRIAL VACUUM HOSE

ROWIN QUALITY ★★★★★



Cuffs: 32, 38, 50 mm



## SPECIFICATIONS

Type	INDUSTRIAL VACUUM HOSE
Material	all plastic Polyethylene-EVA
Temperature range	-25 °C to 60 °C
Bending radius	1 x D
Standard colour	black
Diameter range	every diameter between 22 mm and 63 mm

ROWIN Type	ID mm	OD mm	Average weight g/m	Standard length m
B110VC	25	32	150	10
C220VC	32	40	220	20
C350VC-38	38	47	300	20
C350VC-45	45	55	370	20
C350VC-50	50	60	450	20
C350VC-63	63	74	600	20

## APPLICATIONS

Commercial and industrial vacuum cleaners.  
Car wash and central vacuum installations.  
General-purpose ducting and vacuum hose.  
Other industrial applications.

## ADVANTAGES

- Lightweight, very flexible, crushproof vacuum hose.
- The inside of the hose is very smooth for maximum flow.
- Good chemical and environmental stress crack resistance.
- Long flex life.
- Flexible at low temperature.
- Economical general-purpose hose

